

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/041623 A2

(51) International Patent Classification⁷: **H05H 1/00**

(21) International Application Number:
PCT/JP2004/016179

(22) International Filing Date: 25 October 2004 (25.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-369333 29 October 2003 (29.10.2003) JP
2004-207332 14 July 2004 (14.07.2004) JP

(71) Applicant and

(72) Inventor: **IKENOUCHI, Sumifusa** [JP/JP]; 491-2,
Yanagihara, Hojo-shi, Ehime 7992434 (JP).


(74) Agent: **NAKAJIMA, Shiro**; 6F, Yodogawa 5-Bankan,
2-1, Toyosaki 3-chome, Kita-ku, Osaka-shi, Osaka
5310072 (JP).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PLASMA PROCESSING APPARATUS, CONTROL METHOD FOR PLASMA PROCESSING APPARATUS, AND EVALUATION METHOD FOR PLASMA PROCESSING APPARATUS



(57) Abstract: A plasma processing apparatus comprises: an RF generator operable to output RF power; an impedance matching network operable to receive the RF power; a plasma chamber operable to receive an output from the impedance matching network; a storing unit operable to store information relating to an S parameter of the impedance matching network; and a control unit operable to control an operating condition for the plasma chamber, based on the information relating to the S parameter.



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.